




FlexJet Basic



FlexJet Standard



FlexJet+



HIGH PRESSURE JETTING MACHINES

FLEXJET AND FLEXJET+

SETTING A NEW STANDARD

The FlexJet and FlexJet+ are super compact trailers with a powerful pump suitable for professional unblocking and cleaning of drains and sewers up to 300 mm (FlexJet) or 350 (FlexJet+) mm. The trailer is suitable for professional cleaning companies, councils, building contractors and water authorities.

INTELLIGENT DESIGN

Due to the streamlined and modern design the FlexJet has a low air resistance. Thanks to the use of high strength steel and synthetic material the total weight remains low, making it possible to carry more water.

The light weight FlexJet can be transported by practically all types of vehicle and on a standard driving license. The FlexJet has excellent road holding and maneuvering abilities, thanks to its compact size. The Flexjet+ is a braked trailer. The hose reels are mounted at the perfect working height for ultimate operational comfort. The operator has full control of the FlexJet at the rear. The FlexJet has an integrated 400 litres water tank with a large tool box and lockable cover. The FlexJet+ holds 550 litres of water.

STABLE BUT FLEXIBLE

The innovative construction of the water tank gives a stable road holding both when empty and full by preventing sway during driving. The trailer is very user friendly and is available in various pressure and flow capacities. As the name already indicates this machine can be used flexibly and is well suited to drainage and surface cleaning.

The motor-pump compartment of the FlexJet+ is enclosed and supplied with flame retardant insulation material along with a special cooling system. The FlexJet+ is heavily noise damped. The cover can remain closed during operation and during transport meaning the machine remains free from road dirt and salt.



Flexibility at it's best



- Compact and light weight
- Modern design, easy to use
- Integrated water tanks
- Several configurations available
- For drains and sewers up to 350 mm

TECHNICAL SPECIFICATIONS

	FlexJet Basic	FlexJet Standard	FlexJet+
Operating range	Max 300 mm	Max 300 mm	Max 350 mm
Version	Unbraked, no cover	Unbraked, with cover	Braked, with cover
Engine	Honda, 15 kW (20 HP)	Honda, 15 kW (20 HP)	Honda, 15 kW (20 HP) Honda 18 kW (24 HP)
Pump Rioned/Speck	150 bar / 45 lpm 2200 psi / 10 gpm	150 bar / 45 lpm 2200 psi / 10 gpm	140 bar / 60 lpm 150 bar / 45 lpm 150 bar / 55 lpm 2100 psi / 13 gpm 2200 psi / 10 gpm 2200 psi / 12 gpm
Pressure regulator	Type Speck with automatic bypass	Type Speck with automatic bypass	Type Speck with automatic bypass
Water tank	400 litres	400 litres	550 litres
Fuel tank	15 litres	15 litres	15 litres
Filling reel	35 metres NW 19	35 metres NW 19	35 metres NW 19
HP hose	50 metres NW 13 (1/2")	50 metres NW 13 (1/2")	60 metres NW 13 (1/2")
HP hose reel	Manual drive	Manual drive	Manual drive
Weight	As from 370 kgs	As from 390 kgs	As from 430 kgs
Dimensions (LxWxH)	2815 x 1375 x 1320 mm	2815 x 1375 x 1320 mm	3070 x 1375 x 1320 mm
Nozzles	2 x 1/2" (1 open, 1 blind)	2 x 1/2" (1 open, 1 blind)	2 x 1/2" (1 open, 1 blind)
Accessories	Spraygun and lance	Spraygun and lance	Spraygun and lance
Color	Yellow (RAL 1032) or white (RAL 9010), other colors optionally available		
OPTIONS			
Remote control	RioMote 5 channel radio remote control (gas regulation, pump on/off, emergency stop)		
RioPulse Pulsator	Pump adjustment to send water in pulses through the hose		
Extra hose length	60 or 80 metres NW 13 (1/2") MaxFlow hose instead of 50 metres		
Hydraulic drive (+)	Hydraulically driven HP reel		
2nd high pressure hose reel (+)	Filling reel converted to a second HP hose reel for work with small diameter hose (FlexJet+ only)		
Mechanic freewheel HP hose reel (+)	RioFree mechanical freewheel at the hose reel for coiling off without any resistance		
Hydrant connection	Supply line with hydrant connection for fast filling of the water tank		
Light metal wheels	Light metal wheel rims instead of standard wheel rims		